



Vefráð og samþykkið 10.02.2021

Gönguvarnarlýðun N. 070968-079

EXECUTION CLASS EXC3 IN PRODUCTION

WELDING: WELDING SYMBOL FOR BEARING CONNECTION. SEE EN 1090-2 FOR WELDING SYMBOLS. WELDING SYMBOLS FOR BEARING CONNECTIONS. WELDING SYMBOLS FOR BEARING CONNECTIONS.

TIGHTENING TORQUE: TIGHTENING TORQUE. TIGHTENING TORQUE. TIGHTENING TORQUE.

SPIN DOWN THE NUTS AND WASHERS TO THE TIGHTENING TORQUE. SPIN DOWN THE NUTS AND WASHERS TO THE TIGHTENING TORQUE.

DIAMETER	12	16	20	24	27	30	36
MINIMUM	10	15	20	25	30	35	40

MINIMUM 18 TORQUE. MINIMUM 18 TORQUE. MINIMUM 18 TORQUE.

1. All dimensions and tolerances apply to the drawings as shown. 2. All dimensions and tolerances apply to the drawings as shown. 3. All dimensions and tolerances apply to the drawings as shown. 4. All dimensions and tolerances apply to the drawings as shown.

Revision Date: Issued by: Checked by:

CONTRACTOR:

DESCRIPTION:

PROJECT NAME: Tengivirkid Lækjarfún - Byggingarvirki

PHASE: EXECUTIVE DOCUMENTATION - WORKSHOP DRAWINGS

STEEL STRUCTURE

DESIGNED:

CHECK:

DRAWING NAME: 01. TERMINAL / Tengivirkid

SCALE: 1:25

DATE: 2021.06.47

2345-084-100-07
2020.091.01.1007
SECTION N. ANS
S.L. ÖJF

FORNÁM 2020-11-09

STEEL INSIDE : S235JR (C-2H)
STEEL OUTSIDE : S355J2 (HOT DIP GALV)
SCREWS CLASS: 5.8,8.8,10.9HV