



GERÐ EININGAR	FJOLDI	EINING NR.
130/510	1	1106
DYNGD	STEYPUMAGN (L)	HÆÐ
11.70	4680	1
ALLMENNAR UPPLÝSINGAR, INNVEGGIR		
Staðall:	-	
Steyptustyrkur:	C30	
Steypuferd:	SUS	
Frávik:	+0/-5 mm	
Hula:	-	
Meðhöndlun yforborð:	-	
Aferð ofan í borð:	Slétt	
Annað:	Slétt	
Staðlar:	ÍST EN 260, FS ENV 1991, FS ENV 1992, FS ENV 10080, ÍST EN 13369, ÍST EN 14992	
05.05.01-EB Framleiðsluteikning		

IHLUTIR				
TEG	STK	LYSING	TILVISUN	Lengd/Efn
0164	4	KAN-6000-10-340	HALFEN	
0268	12	Klossi		
0270	24	U 160-155-555		
0271	24	U 200-130-530		

JÄRN BENDING							
HLUT.NR.	STK	GÆÐI	Ø	HLUT.NR.	STK	GÆÐI	Ø
K189	34	Ks500S	6	2985	2	Ks500S	12
3240	2	Ks500S	12	4640	2	Ks500S	12
4655	27	Ks500S	12	5035	8	Ks500S	10
5045	2	Ks500S	12				

JÄRNALISTI - BEYGD JÄRN						
Hlut.nr.	Dver-mál	Klippilengd	Samt	Skissa - mál í mm	Stál-gæði	Rad
V	10	980	13	500 500	Ks500S	20

BR	NR	LYSING	DAGS	SAMP
		Framleiðsluteikning		
			kurtogpi	
			2. JUNN 2010	
Kjðjberg 120 Kjallaraveggir			Yfirfarinn og samþendur uppdráttur, sbr. gr. 17.2 og 19.2 í byggingarreglugerð	
Einingaverksmiðjan hf Breiðáhlíð 110 Reykjavík Tlf. 587 7700				
VERK NR.	TEIKNAB/HANNAÐ	YFIRFARID		
951	BDTH	Steinþór		
DAGS	SANDYKKT			
VEKTOR Hönnun og ráðgjöf ehf. Tlf. 700 26 2429				
MÆLIKVARÐI	TEIKN. NR.	BREYTT		
1:30			31-106	

1-Walls31-106.dwg
PL0: 2010-05-21 15:35 S:\Impact\arkiv\24011051\design\dra