



TÁKN Á TEIKNINGUM:

- ☐ Reykskyrjan
- SL Slökkvitæki
- BO Björgunarop
- LR Loftræsing
- LR Loftræsing
- GK Gólfkótar
- GN Gólfniðurfall
- GSN Gegnumstreymisniðurfall
- 01.01.01 Matshluta og notaninganúmer
- ← Rýmingarætt björgunaropa
- ← Rýmingarleið

10,15  
▼ Kótar á sniðum

HELSTU STÆRÐIR:

Flatarmál húss : 300 m<sup>2</sup>  
Rúmmál húss : 1266,8 m<sup>3</sup>

Einstakir byggingahlutar skulu uppfylla eftirfarandi U-gildi samkvæmt byggingarreglugerð:

Gólf.....0,3 w / m<sup>2</sup>k  
Útveggir.....0,4 w / m<sup>2</sup>k  
Gler og karmar.....2,0 w / m<sup>2</sup>k  
Hurðir.....3,0 w / m<sup>2</sup>k  
Pak.....0,2 w / m<sup>2</sup>k

Útgefandi:	25.01.12	GP	Frumútgáfa
Dagsetning:	25.01.12	At	Skýrning
Aðstöðuhús, Gufuhlíð Reykholti, Blóskógarbyggð			Teknínúmer: 100-02
Aðaluppdrættir: Útlit			Mælikvarði: 1:100
Hannað: Guðjón Þórisson		Teknað: Guðjón Þórisson	
Dagsetning:	25.01.12	Verknúmer:	12 004
Frámstærð: A2		220370-3569	